


Measuring Mass Moment of Inertia as a Simple Pendulum

lb, in, kg, m, sec, in², kg-cm², in-cm
 m = mass
 J_G = mass moment about centroid
 a = distance from pivot to centroid
 g = acceleration of gravity
 τ = time period for one oscillation



*g = 32.174 ft/sec²
 = 386 in/sec²
 = 9.81 m/sec²
 = 981 cm/sec²*

Σ M about P CCW +

Σ M = J φ double dot

$-(mg \sin \phi)a = (J_G + ma^2)\ddot{\phi}$

$(J_G + ma^2)\ddot{\phi} + mga \sin \phi = 0$

non-linear

for small angles $\phi < 15^\circ$, $\sin \phi \approx \phi$

second order ordinary differential equation (ODE)

$(J_G + ma^2)\ddot{\phi} + mga\phi = 0$

linear

assume $\phi = \phi_{MAX} \cos(2\pi f t)$ $\dot{\phi} = -\phi_{MAX} 2\pi f \sin(2\pi f t)$ $\ddot{\phi} = -\phi_{MAX} 4\pi^2 f^2 \cos(2\pi f t)$

~~$-(J_G + ma^2)\phi_{MAX} \cos(2\pi f t) + mga\phi_{MAX} \cos(2\pi f t) = 0$~~

$4\pi^2 f^2(J_G + ma^2) = mga$

using $\tau = 1/f$

$J_G + ma^2 = \frac{mga\tau^2}{4\pi^2}$

$\frac{1}{2} m (v^2 + \omega^2 r^2)$

$2 \times 4 \times 24$ from Notes_07_01 $J_G = 111.9 \text{ lbm.in}^2$

$m = 2.286 \text{ lbm}$ $a = 12.25 \text{ in}$ $20 \tau = 25.74 \text{ sec}$ $\tau = 1.2870 \text{ sec}$


$\frac{mga\tau^2}{4\pi^2} = \left(\frac{2.286 \text{ lbm}}{4\pi^2}\right) \left(\frac{386 \text{ in}}{\text{sec}^2}\right) (12.25 \text{ in})(1.2870 \text{ sec})^2 = 453.52 \text{ lbm.in}^2$

$ma^2 = (2.286 \text{ lbm})(12.25 \text{ in})^2 = 343.04 \text{ lbm.in}^2$

$J_G = 110.48 \text{ lbm.in}^2$ (-1.2% difference)



ω_n object + platform



$\omega_n = \sqrt{\frac{k_r}{J_B}}$

$\omega_n = \sqrt{\frac{J_{PLATFORM}}{k_T}}$

Measuring Mass Moment of Inertia with Torsional Pendulum

Torsional pendulums use a lightweight circular or triangular platform suspended from three light cables as shown below. The platform must be horizontal and the cables must be of equal length. The cables should be attached to the platform equidistant from the center of the platform in an equilateral triangular pattern. Cable attachments need not be at the edge of the platform.

The object should be placed with its center of mass directly over the center of the platform. The centroidal axis of the object must be vertical. The platform must oscillate in pure rotation with small angular displacement about the central vertical axis and must not swing laterally.


This procedure should be used first with an empty platform to determine the mass moment of the platform alone and then repeated with the object centered on the platform to measure the mass moment of the object plus the platform.

Reference: Shigley, J.E. and J.J. Uicker, Theory of Machines and Mechanisms McGraw-Hill, 1995, second edition


$$J_{GO} + J_{GP} = \frac{g(m_o + m_p)r^2\tau^2}{4s\pi^2}$$

- J_{GO} = centroidal polar mass moment of inertia of object
- J_{GP} = centroidal polar mass moment of inertia of platform
- g = acceleration of gravity
- m_o = mass of object
- m_p = mass of platform
- r = radius of cable attachments from center of platform
(not platform radius)
- τ = time period for one torsional oscillation
- s = length of cables

$$J_{GP} = \frac{1}{2} m_p R^2$$



1) platform only
 $M_o = 0$
 $J_{Go} = 0$
 gives J_{GP}



Measuring Mass Moment of Inertia with Platform Pendulum

Platform pendulums use a lightweight rectangular platform suspended from four light cables as shown below. The platform must be horizontal and the cables must be of equal length. Cable attachments need not be at the edge of the platform. Pendulum design should minimize a_o to maximize accuracy.

The object should be placed with its center of mass directly over the center of the platform. The centroidal axis of the object must be horizontal. The platform must swing laterally with small displacement about the centerline of the cable pivots and must not twist or swing axially.

This procedure should be used first with an empty platform to determine the mass moment of the platform itself and then repeated with the object centered on the platform to measure the mass moment of the object plus the platform.

Reference: Mabie, H.H. and C.F. Reinholtz, Mechanisms and Dynamics of Machinery, Wiley, 1987, fourth edition

$$J_{GO} + m_o a_o^2 + J_p = \frac{g(m_o a_o + m_p a_p) \tau^2}{4 \pi^2}$$

J_{GO} = centroidal polar mass moment of inertia of object

J_p = polar mass moment of inertia of platform

g = acceleration of gravity



m_o = mass of object

m_p = mass of platform

a_o = distance from pivot to centroid of object

a_p = distance from pivot to centroid of platform


τ = time period for one oscillation



Measuring Mass Moment of Inertia and Centroid Location Simultaneously

Small objects

- 1) Suspend object by point P_1 and measure τ_1
- 2) Suspend object by point P_2 and measure τ_2
- 3) Measure m
- 4) Measure distances e , ID_B , ID_C



$$\textcircled{1} \quad J_G + m a_1^2 = \frac{m g a_1 \tau_1^2}{4\pi^2} \quad P_1$$

$$\textcircled{2} \quad J_G + m a_2^2 = \frac{m g a_2 \tau_2^2}{4\pi^2} \quad P_2$$

$$4\pi^2(a_1^2 - a_2^2) = g a_1 \tau_1^2 - g a_2 \tau_2^2$$

$$\textcircled{3} \quad a_2 = e - a_1 \quad a_2^2 = e^2 - 2e a_1 + a_1^2$$

$$a_1 = \frac{e(g \tau_2^2 - 4\pi^2 e)}{g(\tau_1^2 + \tau_2^2) - 8\pi^2 e}$$

$$\underline{BG = a_2 - ID_B / 2}$$

$$\underline{CG = a_1 - ID_C / 2}$$

solve for a_1 and then insert in Eq 1 for J_G


Suspended objects

- 1) Suspend object by point P_1 and measure τ_1
- 2) Suspend object by point P_2 and measure τ_2
- 3) Measure m
- 4) Measure distance f *photo*


$$a_2 = f + a_1 \quad a_2^2 = f^2 + 2f a_1 + a_1^2$$

$$a_1 = \frac{f(g \tau_2^2 - 4\pi^2 f)}{g(\tau_1^2 - \tau_2^2) + 8\pi^2 f}$$

then solve for J_G



Measuring Mass Moment of Inertia and Centroid using Multiple Pivots



1) Suspend object by points P_1, P_2, \dots, P_n and measure $\tau_1, \tau_2, \dots, \tau_n$. All points on same body.

2) Measure local coordinates $\begin{Bmatrix} x \\ y \end{Bmatrix}^{P_1}$, $\begin{Bmatrix} x \\ y \end{Bmatrix}^{P_2}$, \dots , $\begin{Bmatrix} x \\ y \end{Bmatrix}^{P_n}$

3) Weigh the object to measure m

$$J_G + m a_i^2 = \frac{m g a_i \tau_i^2}{4\pi^2} \quad a_i^2 = (x^{P_i} - x^{G'})^2 + (y^{P_i} - y^{G'})^2$$

iteratively solve for $\{q\} = \begin{Bmatrix} x^{G'} \\ y^{G'} \\ J_G \end{Bmatrix}$ using $\{\Phi\} = \begin{Bmatrix} J_G + m a_1^2 - m g a_1 \tau_1^2 / 4\pi^2 \\ J_G + m a_2^2 - m g a_2 \tau_2^2 / 4\pi^2 \\ \vdots \\ J_G + m a_n^2 - m g a_n \tau_n^2 / 4\pi^2 \end{Bmatrix}$

$$\{q\}_{k+1} = \{q\}_k - \left([\Phi_q]^T [\Phi_q] \right)^{-1} [\Phi_q]^T \{\Phi\}$$

$$\frac{\partial \Phi_i}{\partial x^{G'}} = -m \left(2 a_i - g \tau_i^2 / 4\pi^2 \right) \frac{(x^{P_i} - x^{G'})}{a_i}$$

$$\frac{\partial \Phi_i}{\partial y^{G'}} = -m \left(2 a_i - g \tau_i^2 / 4\pi^2 \right) \frac{(y^{P_i} - y^{G'})}{a_i}$$

$$[\Phi_q] = \begin{bmatrix} \partial\Phi_1/\partial x'^G & \partial\Phi_1/\partial y'^G & 1 \\ \partial\Phi_2/\partial x'^G & \partial\Phi_2/\partial y'^G & 1 \\ \vdots & \vdots & \vdots \\ \partial\Phi_n/\partial x'^G & \partial\Phi_n/\partial y'^G & 1 \end{bmatrix}$$

```
% t_mult.m - test multiple point measurement of mass moment
% HJSIII, 09.04.11
```

```
clear
```

```
% constants
```

```
m = 96;
```

```
g = 1;
```

```
% experimental values for xg=8, yg=3, JG=2336
```

```
% x, y, t
```

```
xyt = [ 12  2  19.894 ;
        10  5  21.244 ;
        14  5  20.039 ];
```

```
x = xyt(:,1);
```

```
y = xyt(:,2);
```

```
t = xyt(:,3);
```

```
t2term = t.*t /4/pi/pi;
```

```
n = length( t );
```

```
% initial estimate
```

```
q = [ 0 ; 0 ; 0 ];
```

```
% loop
```

```
for iter = 1 : 10,
```

```
% current estimates
```

```
  xg = q(1);
```

```
  yg = q(2);
```

```
  JG = q(3);
```

```
% evaluate residuals
```

```
  a2 = (x-xg).*(x-xg) + (y-yg).*(y-yg);
```

```
  a = sqrt( a2 );
```

```
  PHI = JG + m*a2 - m*g*a.*t2term ;
```

```
% Jacobian
```

```
  par = -m * (2*a - g*t2term) ./a;
```

```
  JAC(:,1) = par .* (x-xg);
```

```
  JAC(:,2) = par .* (y-yg);
```

```
  JAC(:,3) = ones(n,1);
```

```
% update
```

```
  q = q -inv(JAC)*PHI;
```

```
  disp( q' )
```

```
end
```

[Mass Properties Instruments](#)

[Igniter/Squib Circuit Testers](#)

[Mass Properties Lab Services](#)

[Other Products](#)

[Services & Training](#)

[Know-How](#)

[Applications](#)

[About Us](#)

[News & Events](#)

[Contact Us](#)


[Mass Properties Instruments Know-How](#)

[Mass Properties Analysis](#)

Mass Properties Instruments



We design and manufacture a complete range of mass properties measurement instruments and accessories. By employing both strain gauge and magnetic force restoration technology, we have ensured that you will find a solution that's sure to meet your measurement accuracy requirements.

		
Weight & Center of Gravity	Moment of Inertia	Full Mass Properties
		
Dynamic Balancing	Gimbal Balancing	Moment Weight Scales
		
Fixtures & Accessories	Center of Buoyancy	